

FOUR POST LIFTS

GENERAL SERVICE LIFTS

**14,000
POUNDS
CAPACITY**



Easy access to air operated latch release and power unit controls

Self chocking approach ramps and wheel chocks are supplied standard.

All hydraulics and mechanical lifting components are concealed under the runway

Durable powder coat finish

Optional rolling bridge jack with a capacity of up to 7,000 lbs.

Multi-position lock components allow lift to be level at any lock position



Shown: CR14-X 14,000 lbs. capacity
Shown with optional rolling bridge jacks

Engineering Excellence

Forward's U.S. engineers have over 29 years of combined experience designing automotive lifts for service and repair shops. Forward's philosophy is to own our designs rather than use someone else's off the shelf product.

Product Integrity

21st century design tools allow us to create, control and validate our designs to ensure maximum performance. Forward lifts are rigorously tested to meet quality and durability standards. All product families are proof load tested to 1½ times rated capacity and rigorously cycle tested.



**CR14
CR14-X
CRO14
CRO14 EL2
4 Post Series are
Gold Certified Lifts**

Engineered to perform... Built to last!

**FORWARD
LIFT**



Shown: CRO14-X
14,000 lbs. capacity

CRO14 Series

- 14,000 lbs. capacity
- Open front for easy front end vehicle access
- Heavy duty hydraulic cylinder under runway
- Single Point latch release system
- Multi-position lock components in each structural leg allow lift to be level at any lock position
- Jack track is standard feature
- Self chocking approach ramps and wheel chocks are supplied standard
- Up to 7,000 lbs. capacity rolling bridge jacks optional



Four-Post Options:

- Internal Air Line Kit
- Turning Radius Gauges
- Bolt-on Alignment Kit
- Rolling Bridge Jacks
- Power Unit Cover
- 3-Phase Motors
- Drive-Thru Ramps



Shown: CR14-X 14,000 lbs. capacity
Shown with optional rolling bridge jacks.

General Service Lift Specifications	CR14 CR14-X	CRO14 CRO14 EL2
Capacity	14,000 lbs.	14,000 lbs.
Maximum Wheelbase	180" 204"	192-1/2" 212-1/2"
Lifting Height	73-3/4"	73-3/4"
Overall Length	20'-6" 22'-6"	22' 23'-8"
Overall Width	11'-5-1/4"	11'-7"
Width Inside Columns	114-1/4"	117-1/2"
Length between Columns	189-1/4"	201" 225"
Overall Height	7'-4-3/4"	7'-11-3/16"
Runway Width	20"	20"
Runway Height	7"	7"
Width Between Runways	43"	43"
Rise Time	65 seconds	65 seconds
Voltage	208/230	208/230
Motor	2 HP/1Ø*	2 HP/1Ø*
Minimum Bay Size	15' X 25' 15' X 27'	15' X 26' 15' X 28'

*Optional 3-phase available.
Specifications subject to change without notice or liability



Forward Lift
996 Industrial Drive
Madison, IN 47250

Phone: 800.423.1722
Fax: 812.273.7329
www.forwardlift.com



Li# Forward 4Post_GenServ_Cutsheet_2011.07

©2011 Vehicle Service GroupSM
Printed in the U.S.A. All rights reserved. Unless otherwise indicated, Forward Lift, Vehicle Service GroupSM, Dover and all other trademarks are property of Dover Corporation and its affiliates.